FILE NOTATIONS	A section of the sect	
Entered in NID File Entered On S R Sheet Location Map Pinned Card Indexed I W R for State or Fee Land	Checked by Chief Copy N I D to Field Office Approval Letter Disapproval Letter	
COMPLETION DATA: Date Well Completed 8-24-60 OW	Location Inspected Bond released State of Fee Land	-
LOGS FIL	ED	
Driller's Log Electric Logs (No.) E E Mi-L Sonic	R GR-N Micro	**

Scout Report sent Et		Œ
Noted in the NID File		
Location map pinned		
Approval or Disapproval Letter		
Date Completed, P. & A. or operations suspended	************	
Pin changed on location map		
Affidavit and Record of A & P		
Water Shut-Off Test		
Gas-Oil Ratio Test		
Well Log Filed		

Form 9-381a (Feb. 1961)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R366.4 Approval expires 12-31-60. Salt Lake
U-01275
Joe's Valley
Colleen K. Steiner)

r'^

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
lotice - Intention to Plus & Abandon X	

	JULY 21,			,	, 19.29	
Well No. 1 is locate	ed 22 85 ft. f	from S line a	nd 1074 ft.	from E l	ine of sec	18
N E SE Sec. 18	T-15-S	R-6-E	Salt Lake	Base		
(1/4 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)			
Wildcat - Joe's Valley	S	ampete		Utah		
(Field)		unty or Subdivision)		(State or Te	rritory)	

The elevation of the derrick floor above sea level is 10,294 ft. K.B.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was drilled to total depth of 3805 feet, hole logged by Schlumberger to 2684 feet, 9-5/8"OD casing set @ 2584 feet, cemented with 250 sacks cement followed with 125 sacks of bridget, followed with 50 sacks of cement.

We propose to use casing pulling unit, run McCullough Free-Point Indicator, Cut off casing with McCullough Jet String Shot at approximately 2000 feet. Tally on 9-5/8"OD casing totaled 2569 feet, set at 2584.72 feet K.B., Schlumberger log at the time of abandon showed the bottom of casing string to be at 2496 feet. We propose to set 50-sack (50-foot) cement plug at approximately 2000 feet, set 50 sack cement plug at the bottom of 13-3/8QD surface casing, set 50 foot cement plug at surface. To set a well location marker: 4"OD pipe with well location welded on same. Well and location to be abandon.

l understa	nd that this plan of work must receive approval in wri	ing by the Geological Survey before operations may be commenced.
Company	Three States Natural Gas Compa	ny
	P. U. DOX LOU	· · · · · · · · · · · · · · · · · · ·
Address	Scofield, Utah	\sim
	1	
		By W. K. Rriey
		Title District Superintendent
	II S COURDINATING DUR	TING OFFICE: 1968 O = 463339

WO1)	Į.	
		(SUBMIT IN TRIPLICATE)

Unit Jos & Valley

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

CLINDO NOTICES AND DEPOPTS ON WELLS

	August 24,	1960
(INDICATE ABOVE BY CHECK MAR	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
NOTICE OF INTENTION TO ABANDON WELL	-	
NOTICE OF INTENTION TO PULL OR ALIER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	XX_
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	

Well No. 1 is located 2285 ft. from S line and 1074 ft. from line of sec. 18

SE Sec. 18 (36 Sec. and Sec. No.) NE SE Salt Lake Base (Meridian) Joe's Valley Unit (County or Subdivision)

The elevation of the derrick floor above sea level is 10,224 ft. K.B.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and all other important proposed work) Drilled TD: 38051

August 2, 1960 moved in Casing Pulling Unit, shot casing off at 650 feet, set 10 foot cement plug at 650 feet with 20 sacks of cement, pulled 9-5/8=00 casing from well. Set 10 foot cement plug at approximately 315 feet bottom of 13-3/8"CD surface casing, with 10 foot cement plug set in top of surface casing with well location marker extending four feet above ground level. Total cement used in two top cement plugs was 22 sacks cement. Well Plugged and Abandon.

Final report esvering this subject well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. CompanyThree States Natural Gas Company P. C. Box 160 ORIGINAL SIGNED BY Address Scofield, Utah By W. K. RILEY Title District Superintendent